



# ALL OUT BARGAINS **CLEARANCE** VALUES **SALE** BUYS

## Fair Radio Sales Co.

P. O. Box 1105 -- 1016 E. Eureka St.

Lima, Ohio 45802


419/227-6573

**STUFFER #4-80**

ODDS & ENDS, LEFTOVERS, ETC. sold as "reparable" --many at REDUCED prices. Effective thru 8-1-80. Please indicate STUFFER #4-80 when ordering.

### MATRIX PRINTER

VICTOR COMPTOMETER MODEL 1PM-130 MATRIX PRINTER; USED IN POINT-OF-SALE REGISTER SYSTEMS. UNIT HAS THE FOLLOWING FUNCTIONS: LINE FEED, RETURN, AND CARRIAGE FORWARD. WITH SEVEN PRINT SOLENOIDS. CONTROL ELECTRONICS NOT AVAILABLE; NO COVER. SCHEMATIC INCLUDED. POWER REQUIRED: 115 VAC 60 Hz. 8 $\frac{1}{2}$ x10 $\frac{1}{2}$ x4; 13 LBS. UNUSED. \$149.50



\$85.



H-P 522B ELECTRONIC DECADE COUNTER, 10 Hz to 120 KHz FREQ. RANGE; PERIOD: .00001 Hz to 10 KHz. TIME INTERVAL: 10 U-SEC to 100K SEC. RACKMOUNT 19x10 $\frac{1}{2}$ x1 $\frac{1}{2}$ ; SHPG

WT: 60 LBS. USED, REP. \$60. \$35.00

### KLYSTRON POWER SUPPLY



GENERAL MICROWAVE MODEL 303 KLYSTRON POWER SUPPLY; BEAM VOLTAGE VARIABLE FROM -250 TO -400 VOLTS AT 30 to 50 MA. MAXIMUM. REFLECTOR VOLTAGE VARIABLE FROM 0 to -900 VOLTS @ 10 UA. REFLECTOR VOLTAGE INTERNALLY MODULATED AT

1000 HZ SQUARE WAVES ADJUSTABLE UP TO 110 VOLTS PEAK TO PEAK. EXTERNAL MODULATION VIA FRONT PANEL TERMINAL, 100,000 OHM IMPEDANCE. SINUSOIDAL POWERLINE FREQUENCY, VARIABLE FROM 0 to 350 VOLTS PEAK TO PEAK. POWER REQUIRED: 115 VAC 50/60 HZ. SIZE: 11 $\frac{1}{2}$ x13x7 $\frac{1}{2}$  SHPG. WT: 25 LBS. WITH MANUAL (NO SCHEMATIC) PRICE: UNUSED \$45.00 \$25.

### FREQUENCY COUNTER



FR-114/TSM-16 FREQUENCY METER WITH SIX NIXIE TUBE READOUT. COUNTS EVENTS IN THE 20 Hz TO 1 MHz FREQUENCY RANGE. COUNTING INTERVALS: 0.0001, 0.001, 0.01,

0.1, 1.0 or 10 SECONDS. DISPLAY TIME CONTINUOUSLY VARIABLE FROM LESS THAN 1 SEC TO 5 SEC. 100 KHz INTERNAL CHECKING SIGNAL. MANUAL OR AUTOMATIC CYCLING. SINE-WAVE INPUT MUST HAVE HIGH SIGNAL-TO-NOISE RATIO AND AMPLITUDE OF 0.2-50 VRMS; OTHER WAVEFORMS CAN BE APPLIED BUT LEVEL METER MUST BE DISREGARDED. TIME INTERVAL MEASUREMENTS REQUIRE TWO SUCCESSIVE NEGATIVE PULSES 3-8 V. IN AMPLITUDE AND 0.2 TO 10 U-SEC DURATION. 115/230 VAC 50-1000 HZ OPERATION. SIZE: 8 $\frac{1}{2}$ x19x14 $\frac{1}{2}$ ; SH WT: 70 LBS. PRICE: USED, REPARABLE, \$95. \$60.00


### BECKMAN COUNTERS

BECKMAN 7360 UNIVERSAL E/P/UT METER AND TIMER, INDICATES E/P/UT, PERIOD, AND TIME. DC TO 1 MHz RESPONSE; PERIOD: 1 U-SEC TO 10 SEC. SEVEN DECADES. 22x10x16; SHPG. WT: 65 LBS. USED, REP. \$50.



7370 UNIVERSAL E/P/UT METER, SIMILAR TO 7360 EXCEPT DC TO 11.5 MHz. USED, REPARABLE, \$75.


#7360 - \$30. #7370 - \$40.



ROYCO MODULE 515 DATA COUNTER PLUG-IN for particle monitors BEEDE meter relay trips one of two 12 VDC relays at pre-set count rate. Meter FS=1 ma 10K or 100K counts/min. Alarm Override permits push button 100, 1K, 10K, and 100K counts/min. range selection. Uses four printed circuit card. Requires 115 VAC 60 Hz, +30 VDC and -15 VDC. 8 $\frac{1}{2}$ x6x11 $\frac{1}{2}$ , 7 lbs. sh. Used, excellent. Price: w/FS=10K count, \$40.00; \$25.

### KLYSTRON TUBE TESTER

TV-13/POLARAD S-200 MICROWAVE TUBE TESTER, CHECKS LOW POWER EXTERNAL AND INTERNAL CAVITY KLYSTRONS, PENCIL TRIODES, AND LIGHTHOUSE TUBES LIKE 2C39B, 2K25, 6BM6A, QK-SERIES, AND MANY OTHERS. TESTS FOR FILAMENT CONTINUITY, SHORT CIRCUITS, DC VOLTAGES AND CURRENT, LIFE, RF MEASUREMENT. HAS METERS FOR 0-100-500 GRID AND REFLECTIVE VOLTS;



0-1500-5000 BEAM VOLTS; 0-5-100 MILLIAMPS; AND 0-10 FILAMENT VOLTS. FOUR VARIABLE TRANSFORMERS SET REFLECTOR, BEAM, FILAMENT, AND GRID VOLTS. WITH TEST DATA ROLL CHART, COOLING FAN FOR TUBES UNDER TEST, AND TEST LEADS. POWER REQUIRED: 115 VAC 50-60 HZ. 15x19x16 $\frac{1}{2}$ ; 120 LBS SH WT. USED, REPARABLE, \$150.00

Less cables/leads - \$100.

### NOISE GENERATOR



RG-52 MICROWAVE MEGATRON NOISE GENERATOR WITH POWER SUPPLY. USED FOR THE MEASUREMENT OF NOISE FIGURE OR RECEIVER GAIN AND FOR THE CALIBRATION OF STANDARD SIGNAL SOURCES. FLUORESCENT GAS TUBE GIVES 8200 MHZ TO 12400 MHZ FREQUENCY RANGE. HAS THERMOMETER ATTACHED TO AID IN ADJUSTING THE WAVEGUIDE. THE NOISE POWER OUTPUT IS 15.8

DB. WITH AN MOUNTING FLANGE UG-39/U. POWER SUPPLY INPUT 115V. 50-60 HZ. WAVEGUIDE SIZE: 16x5 $\frac{1}{2}$ x1 $\frac{1}{2}$  WT: 2 $\frac{1}{2}$  LBS. POWER SUPPLY SIZE: 11 $\frac{1}{2}$ x7x7 WT: 15 LBS. PRICE: WAVEGUIDE W/POWER SUPPLY, UNUSED \$20.

### GUARD RECEIVER

TRANSISTORIZED GUARD RECEIVER FROM MODIFIED RT-178/ARC-27; REPLACES ORIGINAL TUBE TYPE. UNIT CONTAINS GOLD-WASHED IF, RF, AND AUDIO AMPS; DESIGNED FOR SINGLE GUARD CHANNEL FROM 238 to 248 MHz. 1ST I.F.-25.1 MHz; 2ND I.F.-3.45 MHz. WITH OWN DETECTOR, NOISE LIMITER, AND AVC SECTIONS; 4/2N1745 TRANSISTORS AND 25.1 MHz BANDPASS FILTER. 8x4 $\frac{1}{2}$ x4; 6 LBS. SH. #5821-953-9695, \$14.95



### TS-305B POWER METER



TS-305B/UP POWER METER USED TO MEASURE PEAK RF POWER OF RADIO AND RADAR SETS. FREQUENCY RANGE: 220 to 320 MHz. POWER RANGE: 0 to 50 KILOWATTS INDICATED ON 3 $\frac{1}{2}$ " ROUND MICROAMMETER. INPUT IMPEDANCE: 50 OHMS. POWER REQUIRED: 115 VAC 50-1600 HZ. SIZE: 12x11 $\frac{1}{2}$ x10 $\frac{1}{2}$ ; SHPG. WT: 32 LBS. PRICE: USED, REPARABLE, \$45.

TRANSISTORIZED SIGNAL TRACER FOR USE IN RF, IF, AND AUDIO CIRCUITS. INPUT IMPEDANCE: 30,000 OHMS (AF) AND 50,000 OHMS (RF). WITH 2 $\frac{1}{2}$ " 8 OHM SPEAKER, TEST LEADS, AND 9 V. BATTERY. 2x5 $\frac{1}{2}$ x1 $\frac{1}{2}$ ; WT: 3 LBS. NEW, \$9.95



\$7.95

NON-LINEAR SYSTEMS DIGITAL DC VOLTMETERS WITH RATCHET-TYPE 1 $\frac{1}{2}$ " HIGH READOUTS; AC POWERED. USED, REPARABLE.



MODEL 481 9.999 to 499.9 VDC, \$25.00  
484A 9.999 to 999.9 VDC, AUTO, \$45.00

#481 - \$24. #484 - \$33.



MULTI-VOLTAGE POWER SUPPLIES. THE FOLLOWING POWER SUPPLIES HAVE HARMONIC REGULATED POWER TRANSFORMERS.

SOME OUTPUTS ARE ALSO TRANSISTOR REGULATED. PS736 HAS THE FOLLOWING OUTPUTS: 30V 0.5A 30V 1A, 10V 4A REG., 10V 4A REG., 3.6V 1A REG. THE OUTPUTS ARE INDEPENDENT OF EACH OTHER. 22x6 $\frac{1}{2}$ x6. SH WT 30LBS #2090200 \$12.

PS735 HAS THE FOLLOWING OUTPUTS: 30V 0.5A 30V 1A, 10V 0.5A, 10V 1A. 10V OUTPUTS ARE TRANSISTOR REGULATED. 22x6 $\frac{1}{2}$ x6. SH WT 30LB. PS-55685. \$9. \$11.95

CGC-20409 POWER SUPPLY; INPUT: 115 VAC 60 HZ. OUTPUT: 12 VDC @ 300 MA. (OUTPUT FROM TRANSFORMER: 14 VDC @ 1.5 AMPS.) IN ALUMINUM CASE. SIZE: 8x11x8. WT: 20 LBS. UNUSED, \$2.95 \$7.







**GM-4 AMMUNITION BOOSTER**  
GEARED MOTOR MOUNTED IN-  
SIDE FRAME WITH SHAFT &  
SPROCKETS THAT ARE 3 1/2" DI  
& 3 1/2" APART. MOTOR DESIG-  
NED FOR 24 V. 400 CYC.  
3 PHASE, BUT CAN BE OPER-  
ATED FROM 24 V. 60 CYC  
@ 20 RPM BY USING 4 MFD

CAP. USING HIGHER CAP  
CAP. HIGHER CAP. WILL INCR-  
EASE SPEED AND TORQUE.

STAINLESS STEEL FRAME CAN BE  
REMOVED EASILY. INST. FURNISHED.  
SIZE: 7 1/2 x 2 1/2 x 5 1/2; 10 LBS. GE#9160256-GAM N. \$5.95




**MA-1 RANGE SERVO TEST SET**  
USED FOR TESTING AND TROU-  
BLE SHOOTING AIR FORCE  
TYPE "A" SERIES RANGE SER-  
VOS. SPECIFICALLY, TEST  
PROVIDES MEANS OF MEASUR-  
ING THE VARIOUS OPERATING  
VOLTAGES OF THE RANGE SER-  
VO UNDER TEST AND LOCALIZ-

ING THE TROUBLE WITHIN A RADAR GUNSHOT SYSTEM. CONTAINS 3 1/2" 50 MICROAMMETER WITH 0-60  
0-150 SCALES IN RED FOR ACV & 0-50/500 VDC  
SCALE IN BLK. SELECTOR SWITCHES, INDICATOR  
LIGHTS AND FOUR GORN CONNECTORS 12M & 12F  
WHICH ARE MALE & FEMALE 12 CONTACT ALSO CABLE  
WITH MATCHING DETACHABLE PLUGS.

SIZE: 10 1/2 x 10 7/8 IN ALUMINUM CASE. WT: 18 LBS.  
PRICE: RE-NEW \$15.00

### TUNED CAVITY


**TS-545/UP TUNED CAVITY**,  
DESIGNED TO INDICATE RELA-  
TIVE POWER OUTPUT, FRE-  
QUENCY, RESONANCE, AND  
GENERAL EFFECTIVENESS OF  
A RADAR SYSTEM; RECEIVES  
AND TRANSMIT FROM 1150 TO  
1350 MHZ PULSED. RESON-  
ANCE INDICATED BY NEEDLE  
DEFLECTION OF 3 1/2" ROUND  
0 TO 100 DC MICROAMMETER  
FREQUENCY READ FROM VERNI-  
ER-TYPE DIAL. DECAY: 3.5 DB/U-SEC; SENSITI-  
VITY: 1 DB POWER LOSS FOR 50 YARDS RING-TIME  
POWER REQUIRED: NONE. SIZE: 11 1/2 x 8 x 9 1/2  
SHPG. WT: 40 LBS. PRICE: USED, \$49.50



TS-270 SIMILAR TO ABOVE 2630-2970 MHZ \$39.95

## TAKE 50% OFF MARKED PRICES THESE ITEMS!

### SUGAR READER



**CALBIOCHEM MR340 GLUCOSE  
MINI-READER**; A SMALL  
FIXED-WAVELENGTH (340 NM)  
ULTRAVIOLET PHOTOMETER  
DESIGNED TO MEASURE GLU-  
COSE LEVELS IN BODY FLU-  
IDS. USE OF THE INSTRU-  
MENT INVOLVES THE PLAC-

ING OF A SAMPLE SOLUTION IN A SPECIAL CUVET  
(NOT AVAILABLE) BETWEEN THE KNOWN LIGHT  
SOURCE AND A PHOTORESISTIVE CELL.

REQUIRED: 115 VAC 60 HZ. SIZE: 4 1/2 x 4 1/2;  
SHPG. WT: 6 LBS. PRICE: UNUSED, \$29.95

### DUAL BLOWERS




**DUAL HIGH VOLUME BLOWER**  
210 VOLT 60 HZ 3450 RPM  
1/8 HP MOTOR, 450 CFM  
(ESTIMATED), INLET 3 1/2"

OUTLET 4" DIA. MOUNTED  
ON FRAME 29x6 1/2 IN. (FRAME CAN BE REMOVED)  
WT: 40 LBS. URC#683-KP USED \$12.95

**ROTRON HEAVY DUTY DUAL BLOWER**, 220 VOLT 2 A.  
3 PHASE, 3100 RPM, 50/60 HZ. MOTOR SHAFT  
1/2" DIA. 2-1/2" LG. BLOWER INLET 4", OUTLET  
WITH FLANGE 5 1/2 x 5 1/2. MOUNTING BASE 6 x 9 1/2".  
WT: 40 LBS. URC#4345 USED \$24.95

**TS-170/ARN-5 TEST OSCILLATOR**  
USED FOR PRE-FLIGHT CHECKING  
OF GLIDE PATH RECEIVERS SEN-  
SITIVITY AND AUDIO CHANNELS.  
CRYSTAL CONTROLLED ON THREE  
PREFLECTED FREQ. 332.6, 333.8  
335 MC. MODULATION FREQ. 90  
& 150 CYC. METER IS 2" 0-1  
DC MILLIAMETER. BATTERIES  
REQUIRED 2/1.5 VDC AND 2/  
45 VDC. WT: 29 LBS.  
SIZE: 12 x 16 x 12; UNUSED \$29.50



**EQUIPMENT PARTS -- Write  
your specific needs.**

\*\*\*\*\*

For TV-2 & TV-7 tube  
testers: Meters, \$8 ea.  
Switches, \$3.00 each


For R-390A, R-392, and  
R-388 receivers:  
Slugs \$3 ea. Coils \$7 ea.  
Need other parts? Write  
for quote.

**TMC MSR-4 (CV-591) SSB  
CONVERTER**, 2-32 Mhz.  
30 lbs sh. Used, \$145.

**FLUKE 8300A DIGITAL VM:**  
DC-AC-MV/ohms-BCD out,  
5 1/2 digit. Reparable \$275

**TSI UNIV. COUNTER**, 10 Hz  
to 2.5 Mhz, dual-channel  
time interval, rep. \$125

**TERMS: Cash, MasterCard,  
or VISA. F.O.B. Lima, Oh.**



**TELEMETER PROGRAM SELECTOR**  
USED FOR PAY TELEVISION.  
CHOICE OF 3 PROGRAMS, PRE-  
RECORDED TAPE GIVES PRO-  
GRAM INFO. & AMOUNT OF MONEY  
THAT IS TO BE PUT IN REGIS-  
TER FOR EA. PROGRAM, AS  
SHOWN ON THE COIN REGISTER.  
A 8 MC. SIGNAL IS USED TO  
TRIGGER THE MECHANISM AND  
WE ASSUMED A 35 MC SIGNAL  
CARRIES THE VIDEO AND VOICE  
(ITEMS LISTED BELOW ARE PART  
OF THIS UNIT AND CAN BE  
PURCHASED SEPARATELY.)  
SIZE: 15 x 7 x 7; WT: 25 LBS.  
COMPLETE UNIT #1001/5 \$9.95

**GENERAL RADIO TYPE 371 OLD  
PRECISION POT**, 20K OHMS.  
2 1/2 x 2 1/2; #283-7444, \$2.95

**DE-JUR DUAL POTENTIOMETER**,  
OLD STYLE, 10K OHMS,  
MODEL 2600, 3 1/2 x 4 1/2, \$1.50

**GENERAL RADIO POT TYPE 314**  
S64, 100K OHM, 3 1/2 x 1 1/2, 3/16"  
SHAFT. #7622541, \$2.95

**FAIRCHILD TYPE 746**, 23K OHM  
2.5 WATTS, 1% POT. 1 1/2 x 1 1/2,  
#7630490, \$3.95

**THE MUTER CO. TYPE 433 AC  
POT (REAL ANTIQUE)**, 10K  
5 x 2 1/2; #C10B-2738, \$1.50

**SPECTROL MODEL 300-5041**  
DUAL 100K OHM LINEAR POT;  
5%. 2 1/2 x 1 1/2, #1258, \$4.95



**BELL SINGLE STROKE 50-90  
VOLTS D.C. 2 1/2" GONG.**  
PARTRICK & WILKENS 90VDC \$2


**BELL 20 HZ. 90 V. FOR TEL-  
EPHONE HAND CRANK GENERAT-**  
2 1/2" GONG. WHELOX VP2-1 \$5

**BUZZER 6-12 VDC. 1 1/2 x 1 1/2"**  
EDWARDS#1372 PC90788C \$2

**RELAY SENSITIVE TYPE 300**  
OHMS, OPERATES 2.05 VOLTS  
S.P.D.T. RCA11801-1 \$1.50

**DUAL TESTER: R.P.M.**  
0-1000 & 0-5000 SC.  
VOLTS SCALE 0-18 VDC  
LOWER METER IS FOR  
TESTING SPARK ADVAN-  
CE. ALSO PUG FOR  
TRANSUDOR ADAPTER.  
USES TUBES 1 EA. 2D2,  
6AL5, 6AU6, 5696 AND  
2/0A2. TWO 4 1/2" METER  
500 MUA CHROME. COND. USED  
SIZE: 13 x 5 x 5; WT: 13 LBS.  
LESS TUBES \$9.95 W/TUBES \$15

No. 336  
2/0A2. TWO 4 1/2" METER  
500 MUA CHROME. COND. USED  
SIZE: 13 x 5 x 5; WT: 13 LBS.  
LESS TUBES \$9.95 W/TUBES \$15




**COIL & CONDENSER  
TESTER W/OHMETER**  
FOR AUTOMOTIVE USE  
VIBRATOR SUPPLIES  
THE NORMAL CURRENT  
TO THE COIL AT PRO-  
PER DWELL. CAPACI-  
TORS ARE CHECKED  
FOR CAPACITY, LEAK  
AGE, RESISTANCE ET  
ASIDE FROM THESE  
METER ALSO HAS A  
100,000 OHMMETER  
#332  
SCALE. METER IS 4 1/2" SATIN/  
CHROME 500 MUA 2% ACCURACY.  
VOLTAGE REQ. 6/12 VDC #332  
W/TUBES 1/12AU7, 1/0A2, 1/6X4  
SIZE: 14 x 5 x 6; 10 LBS \$14.95 U

**MODEL #337 TACH &  
VOLT-METER: FOR AUT  
OMOTIVE USE. TACH  
RANGES 0-1000 & 0-  
5000 RPM. VOLT DC  
RANGE 0-18 ALSO  
PROVISIONS FOR  
PLUGGING IN TIMING  
LITE. W/TUBES 1/  
0A2, 1/2D21. METER  
4 1/2" CHROME 500 MUA  
FOR 6/12 VDC OPER.  
SIZE: 13 x 5 x 5; 8 LBS. \$14.95 U**

**COIN REGISTER  
MECHANISM**  
CONTAINS TWO  
ACTUATING  
PLATE TYPE SEL  
ENOLDS 300 AND  
1200 OHMS.  
CRAMER 115V60 CYCLE, 5 RPM  
SYNCHRONOUS MOTOR, OPEN FRAME  
115 V. 60 CYC. GEARED MO-  
TOR, WITH GEARED MECHANISM  
AS USED IN COIN OPERATED TV  
PROGRAM SELECTOR SYSTEM.  
ALSO GEARS, LITES COIN NUMB-  
ERING RECORDING DIALS ETC.  
SIZE: 7 x 5 x 6; WT: 8 LBS.  
TELE-REG.#1004 RE-MOVE \$5

**TAPE MAGAZINE 1/4"**  
66 FT. CONTINUOUS  
LOOP TYPE. HAS REC-  
ORDING HEAD, FOR  
20 RPM OPERATION.  
USED WITH COIN  
REGISTER DISCIB-  
ED ABOVE. (NOT MOTORIZED)  
SIZE: 4 1/2 x 3 1/2; WT: 2 LBS.  
TEL-TAPE#1003 RE-MOVE \$3.00

**TELEMETER CHASSIS; WITH 4"  
APEAKER, 2 PLATE RELAYS, R.F.  
COILS FOR 8 MC. 115 V. 60 CYC  
POWER SUPPLY, OUTPUT 150VDC  
100MA & 6.3V 3A. 8135 CRYST.  
W/TUBES 3/6UB, 6BE6, 6BA8 &  
12BH7 1EA. SIZE: 10 1/2 x 6 1/2; 10 LBS  
TELE-CHASSIS#1002 RE-MOVE \$7**



**TRANSMITTER P.A. COIL VARI-  
OMETER TYPE 5.3-7MC.**  
4 x 2 1/2" #7249 RE-MOVED \$2

**TRANSMITTER OSC. M.O. COIL  
FOR 7-9.1 MC. #6032 REM \$1**

**RECEIVER I.F. COIL 2830KHZ**  
7277 6-9.1 MHZ 1ST I.F. \$2  
7278 NOT AVAILABLE. 7277  
CAN BE USED F/7278, RE-MTG.  
7279 6-9.1 MHZ 3RD IF. \$2.  
5856 6-9.1 " OSC. \$1.50  
6234 6-9.1 " RF SECTION \$5

**RECEIVER COILS 1415 MHZ**  
7274 3-6 MHZ. 1ST I.F. \$2  
7275 " " 2ND I.F. \$2

**T-4/FRC TRANSMITTER COILS**  
PLUG-IN TYPE WITH BANANA  
JACKS

NUMBER	FREQUENCY KHZ	
1535	2800-2850	\$4
1541	3516-3800	\$4
1537	5845-5000	\$4
1548	5195-6000	\$4
1549	7180-7573	\$4
1538	7573-7600	\$4
1542	9230-10000	\$4
1543	11720-12000	\$4
1544	14850-15000	\$4

STOCK# USE T-4 & COIL #

**COILS-MIXED-NUMBERS-TRANS.**  
WITH BANANA JACKS.  
NUMBER FREQUENCY KHZ  
2354 3550-4500 \$4  
2356 5750-7200 \$4  
2359 12.7-18000 \$4  
20113 2000-3500 \$4  
#5950 LARGE COILS & (NUMBER



**MEISSNER PLUG-IN COILS, 3  
IN SET INCLUDING OSC. GRID,  
OSC. PLATE, AND BUFFER.**

No.	KHZ	PRICE
3C368-14	1000-1170	\$3.00
3C2500-51	2040-2410	2.00
3C2500-52	2395-2835	2.50
3C2500-17	7000-7000	2.50

STANDARD 4, 5, 6 PRONG SOCK-  
ETS REQUIRED FOR EACH SET.

RU-18 & RU-19 RECEIVER COIL SETS & ACCESSORIES		
CW	455 KHZ	PRICE
CW-47068	850-1330	\$6
CW-47869	1330-2040	\$5
CW-47070	2040-3000	\$5
CW-47072	4000-6000	\$5
CW-47075	9050-13575	\$5
CW-47108	540-830 & 5200-7700	\$8
CW-47204	540-830 & 2040-3000	\$8
CW-46011	MOUNTING BASE	\$3
CW-62007	JUNCTION BOX	\$3
CW-23012	REMOTE TUNER	\$3
CW-23087	SWITCH BOX	\$3
CW-22266	TEST METER	\$6

**WILCOX RECEIVER BFO COIL**  
455 KHZ, DUAL AIR TRIMMER  
WITH 1/4" SHAFT TOP OF CAN  
229644.4 \$2.00

**BC-683 LCU3C COIL** \$2.00

**BC-3480 RECEIVER I.F. COILS**  
1ST 9A1952 \$147 \$3.00  
2ND 9A1953 \$148 \$3.00

**BUD TRANSMITTING PLUG-IN  
COILS MOUNTED ON FIVE PIN  
CERAMIC BASE,**  
3C804 40 METERS \$2.00  
3C805 20 " \$3.00